

DZ series

HIGHLIGHTS

- Binocular models with optional photo ports
- Six standard configurations or customized configurations
- Ergonomic tilting head from 0 to 35° tilting or fixed 20° inclined head
- EWF10x/22mm eyepieces
- Three central zoom units from 4 to 320x
- Fields of view from 55 to 1.4 mm
- Ergonomic rack & pinion, universal stand or articulated arm stands
- Transmitted and incident 3 W LED illumination
- 100 W epi-fluorescence
- 10 years warranty

TECHNICAL SPECIFICATIONS

EYEPIECES

Pair of EWF 10x/22 mm eyepieces

HEAD

- Ergonomic binocular 0-35° tilting head
- Binocular 20° tilted head
- Diopter ± 5 adjustment on both eyepieces
- Interpupillary distance from 55 to 75 mm
- Optional photo ports for one or two cameras

CENTRAL ZOOM UNIT

Three central zoom units are available:

- 1:6.3 for total magnifications from 8 to 50x
- 1:8 for total magnifications from 8 to 64x
- 1:10 for total magnifications from 8 to 80x

COMMON MAIN OBJECTIVE

- Standard configurations are supplied with a 1x plan apochromatic Common Main Objective, WD 78 mm
- Other plan apochromatic Common Main Objectives 0.5x (WD 126 mm) and 2x (WD 33 mm) are also available

All optics have an anti-reflection coating for maximum light throughput and are anti-fungus treated

STAND

- Large ergonomic stand with \varnothing 100 mm object plate and two object clamps
- Coarse adjustment with adjustable friction
- A universal stand and articulated arm stands without illumination are also available



• Customized configuration model

(DZ.0800, 2x DZ.3010, DZ.2025, DZ.9005, DZ.9010, DZ.4010 and DZ.5020)

ILLUMINATION

- Supplied with transmitted and incident 3 W LED illuminations with a built-in 100-240 V power supply
- Both illuminators can be used simultaneously and the light intensities can be adjusted separately

PACKAGE CONTENT

- Supplied with power cord, dust cover, a spare fuse and user manual
- All packed in a polystyrene box

• Ergonomic head



STANDARD CONFIGURATIONS

- All six standard configurations are equipped with EWF10x/22mm eyepieces, 1x plan apochromatic Common Main Objective
- All six standard configurations are equipped with DZ.5040 rack & pinion stand with incident and transmitted LED illumination

MODELS (STANDARD)

	Binocular 20° head	Binocular Ergo 0 to 35° tilting	Magnifications from 8 to 50x	Magnifications from 8 to 64x	Magnifications from 8 to 80x
DZ.1100		•			•
DZ.1105	•				•
DZ.1800		•		•	
DZ.1805	•			•	
DZ.1600		•	•		
DZ.1605	•		•		

All equipped with EWF10x/22mm eyepieces



• DZ.0800/DZ.2020/DZ.3010(2x)/DZ.4005/DZ.5040



• Customized specification fluorescence model

MAGNIFICATIONS AND FIELD OF VIEWS FOR STANDARD CONFIGURATIONS

MODEL	Zoom indication	0.5x objective WD 126 mm		1.0x objective WD 78 mm standardly supplied		2.0x objective WD 33 mm	
		Total magnification	Field of view	Total magnification	Field of view	Total magnification	Field of view
DZ.1100 / DZ.1105 DZ.1800 / DZ.1805 DZ.1600 / DZ.1605	0.8x	4x	55	8x	27.5	16x	13.7
	1.0x	5x	44	10x	22	20x	11
	1.5x	7.5x	29.3	15x	14.6	30x	7.3
	2.0x	10x	22	20x	11	40x	5.5
	3.0x	15x	14.6	30x	7.3	60x	3.6
	4.0x	20x	11	40x	5.5	80x	2.7
	5.0x	25x	8.8	50x	4.4	100x	2.2
	6.0x	30x	7.3	60x	3.6	120x	1.8
	6.4x	32x	6.8	64x	3.4	128x	1.7
	7.0x	35x	6.3	70x	3.1	140x	1.5
8.0x	40x	5.5	80x	2.75	160x	1.4	

BUILD YOUR OWN MICROSCOPE

A customized DZ series stereo microscope can be configured to customer's specifications by choosing one of the three central zoom units DZ.0630, DZ.0800 or DZ.1000 and adding the necessary components for the application. Pair of eyepieces, an ergonomically 5 to 35° tilting head or fix

20° inclined head, a 0.5x, 1x or 2x Common Main Objective (CMO), a large ergonomic LED stand, a boom or an articulated arm stand. Other accessories like a photo/camera unit or dual iris diaphragm can complete the configuration

ACCESSORIES & SPARE PARTS

CENTRAL ZOOM UNITS

- DZ.0630** Central Zoom Unit 1:6.3 unit with magnifications from 8 to 50 times
- DZ.0800** Central Zoom Unit 1:8 unit with magnifications from 8 to 64 times
- DZ.1000** Central Zoom Unit 1:10 unit with magnifications from 8 to 80 times

HEADS

- DZ.2020** Ergonomic binocular 0-35° tilting head without eyepieces
- DZ.2025** Binocular 20° tilted head without eyepieces
Interpupillary distance from 55 to 75 mm.

EYEPIECES

- DZ.3010** EWF 10x/22 eyepiece, 1 piece
- DZ.3012** EWF 10x/22 eyepiece with cross hairs, 1 piece
- DZ.3015** WF 15x/16 eyepiece, 1 piece
- DZ.3020** WF 20x/12 eyepiece, 1 piece

DIAPHRAGM

- DZ.9010** Double iris diaphragms for increased depth of field

OBJECTIVES

- DZ.4003** Plan Common Main Objective 0.3x. WD 276 mm
 - DZ.4005** Plan apochromatic Common Main Objective 0.5x. WD 126 mm
 - DZ.4010** Plan apochromatic Common Main Objective 1.0x. WD 78 mm
 - DZ.4020** Plan apochromatic Common Main Objective 2.0x. WD 33 mm
- All optics are anti-fungus treated and anti-reflection coated for maximum light throughput*

STANDS

- DZ.5020** Universal stand without illumination.
Dimensions 460(h) x 280 (l) x 400 (d) mm
- DZ.5040** Ergonomic stand with transmitted and incident LED illumination.
Coaxial coarse and fine adjustments, 100 graduations, 0.015 mm per graduations
- 65.980** Articulated arm stand for mounting on table without head holder (65.981)
- 65.981** Head holder 76 mm for DZ series and black articulated arm stand (65.980)
- NZ.9025** Articulated arm stand with table clamp (without DZ head holder 65.981)
- NZ.9027** Articulated arm stand with heavy stand (without DZ head holder 65.981)
- NZ.9042** Stand with rotating mirror and transmitted LED illumination
- NZ.9030** Boom (double arm) stand with heavy stand (without head holder NZ.9090)
- NZ.9032** Boom (double arm) stand with table clamp (without head holder NZ.9090)
- NZ.9090** Head holder (for NZ.9020, NZ. 9030 and NZ.9032)

FLUORESCENCE ATTACHMENT

- DZ.9050** Attachment for fluorescence with 100 W mercury vapor illumination with GFP-B and GFP-LP filter sets and one 23.2 mm photo port.
Supplied with power supply
 - DZ.9060** Filter cube with GFP-B for Blue excitation, EM band pass filter (EX 460-500, DM 505, EM 510-560)
 - DZ.9061** Filter cube with GFP-L for Blue excitation, EM long pass filter (EX 460-500, DM 505, EM 510)
- Other fluorescence filters available on request*

MISCELLANEOUS

- DZ.9020** Large 185 x 145 mm stage with mechanical X-Y
50 x 50 mm stage, to be moved by hand
- DZ.9040** Darkfield attachment for DZ.5040
- DZ.9045** Polarizer, 360° rotatable, to be mounted on
Common Main Objectives of DZ series
- DZ.9047** Polarizer, 360° rotatable, to be placed on the stage
- DZ.9005** Photo port attachment with one 23.2 mm tube
- DZ.9007** Photo port attachment with two 23.2 mm tubes
- DZ.9013** C-mount 1x objective for insertion into photo port attachments
- AE.1900** Glass object plate, ø 100mm
- AE.1903** Acrylic white/black object plate ø 100 mm
- 50.875** Adjustable GEM clamp
- AE.5130** Universal SLR camera adapter with 2x projection lens for
23.2 mm tubes. Needs T2 adapter
- AE.5025** T2 adapter for Nikon D digital SLR cameras
- AE.5040** T2 adapter for Canon EOS digital SLR cameras

Other T2 adapters on request

- AE.1385** 100 W HBO mercury vapor bulb for fluorescence
- SL.5520** LED replacement for incident LED illumination of DZ.5040 stand
- AE.1112** Micrometer slide, 50 mm/50 divisions
- PB.5245** Lens cleaning paper, 100 sheets per pack
- PB.5274** Isopropyl alcohol 99% (200 ml)
- PB.5275** Cleaning kit: lens cleaning fluid, lint free lens tissue, brush, air blower, cotton swabs

WD = working distance