

CMEX-1

USB-2 camera with CMOS sensor
 DC.1300c

HIGHLIGHTS

- Entry level camera for amateur, education and laboratories
- 1.3 Mpix CMOS color USB 2.0 camera
- 1/2.5" sensor, 1272 x 952 pixels
- ADC 10 bits, color depth 24 bits
- Low signal/noise ratio
- USB 2.0 interface



● CMEX

TECHNICAL SPECIFICATIONS

Sensor	CMOS 1/2.5 inch
Pixels	1272 x 952 pixels, 1.3 Mpix
Scan mode	Progressive, rolling shutter
Pixel size	2.2 µm x 2.2 µm
Filter	RGB
Mount	C-mount
Max fps	Up to 15 frames per second (1272 x 952 pixels) Up to 30 frames per second (632 x 472 pixels)
ADC	10 bits
Color depth	24 bits
Sensitivity	1.3 V/lux-sec @ 550 nm
Exposure	Automatic or manual, from 1 ms to 300 ms
White balance	Automatic/manual
Dynamic range	72 db
S/N max	55 db
Data interface	USB 2.0 at 480 Mb/s
Operation	0 – 60° C, 45-85 % humidity
Storage temperature	-20 to 70° Celsius
Supplied with	0.45x objective with C-mount, USB 2.0 cable, 30 and 30.5 mm adapters for stereomicroscopes, 76 x 24 mm calibration slide (1mm/100), CD ROM with ImageFocus 4 software, carton box
Software	Windows7 and higher (32 and 64 bit configurations)
Product number	DC.1300c

	Number of pixels (MP)	Sensor	Sensor size (inches)	Pixels size (µm)	Resolutions	Max. frames (p/sec)	Grayscale conversion	Color rendering	Signal/ Noise(db)	Dynamic (db)	Sensibility V/lux-sec (at 550 nm)	Product number
CMEX-1	1.3	CMOS	1/2.5"	2.2x2.2	1272x952 632x472	15 30	10 bits	24 bits	55	72	1.3	DC.1300c

The CMEX cameras are supplied in a carton box with USB-2 cable, 30.0 and 30.5 mm to 23.2 mm conversion adapters for use with stereo microscopes, 1mm/100 (10µm/division) calibration slide and a 0.45x C-mount objective